



online controller

675€



FTX-25K

679€



FTX-25JV

725€



FTX-35K

709€



FTX-35JV

CONJUNTO SPLIT DE PARED SERIE K/G				TX25K	n!	TX35K	n!	TX25JV	TX35JV
Capacidad	Refrigeración	(Min.-Nom.-Máx.)	W	1.300-2.500-3.000		1.300-3.500-4.000		1.300-2.500-3.000	1.300-3.300-3.800
	Calefacción	(Min.-Nom.-Máx.)	W	1.118-2.150-2.580		1.204-3.010-3.440		1.120-2.150-2.580	1.120-2.840-3.270
Consumo	Refrigeración	Nominal	W	740		1.070		730	980
	Calefacción		W	690		1.000		690	930
Conexiones	Líquido		mm	ø 6,4 (1/4")		ø 6,4 (1/4")		ø 6,4 (1/4")	ø 6,4 (1/4")
	Gas		mm	ø 9,5 (3/8")		ø 9,5 (3/8")		ø 9,5 (3/8")	ø 9,5 (3/8")
Alimentación eléctrica				I/220V		I/220V		I/220V	I/220V
Nº hilos de interconexión				3 + T		3 + T		3 + T	3 + T
EER / COP	Refrig. / Calef.			3,37 / 4,40		3,30 / 4,00		3,42 / 4,06	3,37 / 3,76
Etq. efic. energ.	Refrig. / Calef.			A / A		A / A		A / A	A / A
SEER / SCOP	Refrigeración / Calefacción			6,33 / 4,70		6,42 / 4,74		5,40 / 4,27	5,77 / 4,57
Etq. efic. estac.	Refrigeración / Calefacción			A++ / A++		A++ / A++		A+ / A+	A+ / A+
Carga de diseño (Pdesign)	Refrigeración		kW	2,50		3,50		2,50	3,30
	Calefacción (-10°C)		kW	2,40		2,80		2,40	2,80
Consumo energía anual estacional	Refrigeración		kWh	138		191		155	204
	Calefacción		kWh	715		827		746	945

UNIDADES INTERIORES DE PARED SERIE K / G				FTX25K	n!	FTX35K	n!	FTX25JV	FTX35JV
Caudal de aire	Refrigeración	(A/B/SB)	m³/min	9,2 / 5,0 / 3,9		9,3 / 5,8 / 4,4		9,2	9,3
	Calefacción			10,0 / 6,0 / 4,3		12,1 / 6,5 / 6,5		9,7	10,1
Velocidades del ventilador			Nº	5 + A + S		5 + A + S		5 + A + S	5 + A + S
Dimensiones	Alto		mm	283		283		283	283
	Ancho		mm	770		770		770	770
	Fondo		mm	225		225		198	198
Peso			Kg	7,0		7,0		7,0	7,0
Nivel de potencia acústica			dBA	55		58		56	57

MODELO			TX25K	n!	TX35K	n!	TX25JV	TX35JV
Longitud máxima de tubería (L)			m	20	20		15	15
Diferencia de nivel máxima (H)			m	15	15		12	12