

FRESH

A+/A
19dB

Z09EM

Inverter

510€



FRESH

A+/A
19dB

Z12EM

520€



			Z09EM.SSW E09EM.UA3	Z12EM.SSW E12EM.UA3	E18EM.SSM E18EM.UL2	P24EL.SS2 P24EL.NS2
			Z09EM.NSW	Z12EM.NSH	E18EM.NSM	P24EL.UUE
Interior						
Capacidad (mín.-nom.-máx.)	Refrigeración	W	890 / 2500 / 3700	900 / 3500 / 4040	900 / 5000 / 5400	900 / 6800 / 7420
	Calefacción	W	890 / 3200 / 4100	890 / 3800 / 5100	900 / 5400 / 6100	900 / 8000 / 8640
	Calefacción -7°C	W	3000	3600	3800	4850
Consumo	Refrigeración	W	730	1.120	1.720	2.193
	Calefacción +7°C	W	950	1.040	1.540	2.285
EER		W/W	3,42	3,13	2,91	3,10
S.E.E.R			5,7	5,8	5,3	6,1
P design Refrigeración		Kw	2,5	3,5	5,0	6,8
COP		W/W	3,37	3,65	3,51	3,50
SCOP			3,8	3,8	3,8	3,8
P design Calefacción		Kw	2,3	3,2	3,8	5,5
Etiqueta Energética	Frío / Calor		A+ / A	A+ / A	A / A	A++ / A+
Consumo anual de energía	Frío / Calor	kWh	154 / 847	211 / 1179	330 / 1400	391 / 2027
Presión sonora (S/B/M/A)	Refrigeración	dB(A)	20 / 25 / 33 / 39	20 / 25 / 33 / 39	29 / 35 / 40 / 42	29 / 35 / 40 / 45
	Calefacción	dB(A)	28 / 33 / 39	28 / 33 / 39	35 / 40 / 42	35 / 40 / 45
Caudal de aire (S/B/M/A/max)	Refrigeración	m³/min	3 / 4,5 / 6 / 7,5 / 9	3,5 / 5,5 / 8 / 10 / 12	8 / 10,5 / 13 / 15 / 19	8 / 11 / 14 / 15 / 23
	Calefacción	m³/min	5 / 6 / 8	6,5 / 8 / 10	10,5 / 13 / 15	11,5 / 15 / 18,5
Alimentación eléctrica		Φ / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Cable alimentación		N x mm²	3 x 1.0	3 x 1.0	3 x 1.5	3 x 2.5
Cable interconexión		N x mm²	4 x 0.75 (Including Earth)	4 x 0.75 (Including Earth)	4 x 0.75 (Including Earth)	4 x 1.0 (Including Earth)
Dimensiones		mm	756*265*184	798*292*214	885*296*236	1090*330*248
Peso neto		kg	7,4	8,5	9,5	14